

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ : C07C 29/136, 31/20		A1	(11) International Publication Number: WO 99/52845 (43) International Publication Date: 21 October 1999 (21.10.99)
(21) International Application Number: PCT/EP99/02297 (22) International Filing Date: 2 April 1999 (02.04.99) (30) Priority Data: 9800276 9 April 1998 (09.04.98) BE (71) Applicant (for all designated States except US): PANTOCHIM S.A. [BE/BE]; Parc Industriel, Zone A, B-7181 Feluy (BE). (72) Inventors; and (75) Inventors/Applicants (for US only): BERTOLA, Aldo [IT/IT]; Via Luigi Illica, 5, I-20121 Milano (IT). RANGHINO, Giovanni [IT/IT]; Via 7a Strada, 27, I-20090 San Felice-Segrate (IT). (74) Agent: SARPI, Maurizio; Studio Ferrario, Via Collina, 36, I-00187 Roma (IT).			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: PROCESS FOR THE PRODUCTION OF BUTANEDIOL			
(57) Abstract Process for the production of 1,4-Butanediol by vapour phase catalytic hydrogenation of gamma-butyrolactone, maleic and/or succinic anhydride methyl esters or mixtures of gamma-butyrolactone and maleic and/or succinic anhydride esters, characterised by the fact that, in the operating conditions described in the process, by feeding hydrogen gas containing carbon monoxide to the reaction, a concomitant production of synthesis methanol is obtained, and conversion values relating to methanol production are improved.			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Process for the production of Butanediol.

Description.

The present invention relates to a process for the production of 1,4-butanediol by vapour phase flow catalytic hydrogenation of gamma-butyrolactone, succinic or maleic anhydride methyl esters, or mixtures thereof, wherein the hydrogen flow is enriched with CO, so as to accomplish an extra production of synthesis methanol, with a consequent increase in the yield of the final product.

It is known from the prior art that there exist many processes for the preparation of butanediol using dicarboxylic acid esters with four carbon atoms as starting materials.

In USSR Patent N°400,567 a copper chromite catalysed liquid phase conversion of esters into BDO at temperatures ranging between 280 and 300°C and 300 bar pressure is given.

In US Patent N°4,613,707 a conversion of diethylsuccinate into BDO at 200°C T and 135 bar pressure with a mainly copper and aluminium borate catalyst is given.

In US Patent N°2,079,414 a vapour phase hydrogenation of esters is given, on a copper chromite type catalyst and temperatures ranging between 300 and 400°C.

In US Patent n°2,040,944 a broad description of both liquid and vapour phase ester hydrogenations is given, using copper chromite catalysts. In one example, a liquid phase butyl succinate hydrogenation at 207 bars is described.

In US Patents n°'s 4,584,419 and 4,751,334, assigned to Davy Mc Kee Ltd. (U.K.) processes for the large scale production of BDO are described and they involve four carbon dicarboxylic acid ester hydrogenations.

The operating conditions of the hydrogenations claimed in the patents assigned to Davy McKee Ltd. are pressures ranging between 25 and 75 bars, and temperatures between 150° and 240 °C, in the presence of a stabilised cuprous chromite type catalyst in its reduced form.

Moreover in the latter patent it is stated that the process which is claimed in it yields a 79.3% conversion into the desired product, after the first stage.

There is no indication of the overall conversion, but it is not at all unfair to be sure that it is somewhat lower than the above value.

Likewise, a 78.3% overall conversion is obtained in the process claimed in the former patent.

Clearly, as the above values hold on an industrial scale, they leave much room for substantial improvements.


Aim of the present invention is therefore to propose a process which allows much higher conversion rates, therefore increases the profitability of its application to the plant scale.

Another aim of the present invention is that of proposing a methodology for the contemporaneous production of BDO and methanol (MOH) operating in specific conditions and on suitable catalysts.


The above aims are accomplished by a process for the production of 1,4-butanediol by vapour phase selective hydrogenation of gamma-butyrolactone, maleic or succinic anhydride methyl esters or mixtures of gamma-butyrolactone with the esters thereof, characterised by the fact that synthesis methanol is coproduced by feeding hydrogen gas enriched with carbon monoxide to the reaction.

According to the process of the present invention, methyl dicarboxylic acid esters with four carbon atoms, e.g. dimethylmaleate (DMM) or dimethylsuccinate (DMS), gamma butyrolactone (GBL), or mixtures of GBL with the esters thereof, are utilised as starting materials for the production of BDO.

Methanol synthesis is accomplished by feeding carbon monoxide together with hydrogen gas. The reaction by which BDO forms thanks to the hydrogenation of an ester like DMS for example, is given by the following equation:



The MOH synthesis reaction is given by the following equation:



MOH that forms in reaction (A) is recovered to be fed to an esterification unit .

However from a practical viewpoint, part of the MOH is lost either literally or in the form of by-products. MOH real losses, about 0.1 to 0.3 mols for each mol of BDO produced, may even be compensated by MOH formation according to reaction (B), this making the production unit completely self-sufficient in terms of MOH.

The most important aspect is the neat improvement given by the process object of the present invention in so far as the yield of reaction (A) is concerned, more than its self-sufficiency in terms of MOH consumption, the latter being nevertheless a not unimportant factor.

Surprisingly, the MOH synthesised which adds up to the MOH produced in reaction (A) is not of any hindrance to the BDO synthesis reaction as it would be expected to be. Instead it results to have a remarkably positive effect on the conversion of the ester and/or GBL of the shot.

The surprising observation stated above may be explained by dint of the protective action exerted onto the active sites of the catalyst by the methanol synthesis.

It may be significant that the catalyst employed in the hydrogenation reaction is of either the exact same or similar type as that employed in methanol synthesis, e.g. of the copper-zinc oxide, or cuprous chromite type, this ensuring a compatibility and ease of coexistence of the two reactions in the same vessel.

In the process which is object of the present invention, the typical operating conditions for this reaction are as follows:

Reaction type:	adiabatic
Molar ratio between H_2 and ester:	from 200 to 800, preferably from 200 to 500
Molar ratio between CO and	

shot ester:	from 0.1 to 1.0 preferably from 0.2 to 0.4
Operating pressure:	from 75 to 120 bars, preferably from 80 to 100 bars
Operating temperature:	from 170 to 230°C preferably from 190° to 210 °C
Type of catalyst:	Copper/Zinc oxide or cuprous chromite
Liquid Hourly Space Velocity:	from 0.1 to 1.0 hr ⁻¹ , and averagely from 0,3 to 0.5 hr ⁻¹

These and other features will be more readily apparent from the following description of a preferred not limiting embodiment of the invention with reference to the accompanying drawing in which a scheme (Fig. 1) of the production process is shown.

The following operating conditions refer to a starting material made up of a mixture of GBL and DMS in 70:30 proportions by weight.

The feed mixture (Line 1) is fed to vapouriser 3, together with a liquid recycle mixture (Line 2), that contains GBL from fractionation unit 22. In vapouriser 3 both the feed (Line 1) and the recycle (Line 2) come to contact with a hot hydrogen stream (Line 4), and they vapourise. In the gas stream coming out of the vapouriser (Line 5) the molar ratio between hydrogen and ester is 300:1, the molar ratio between CO and ester is 0.2, temperature is 190°C and pressure is 80 ATE.

Such stream feeds Stage I of reaction 6 where there is a copper-zinc oxide type catalyst with a surface area never any smaller than 40 m²g⁻¹.

At the inlet of Stage II in reaction 7, temperature is taken down to approx. 190°C by injection of a cold hydrogen stream (Line 7). Overall Liquid Hourly Space Velocity in the two reaction stages is 0.35 hr⁻¹.

At the inlet of Stage II in reaction 8, DMS conversion results to be higher than 98%, while GBL conversion in the feed is higher than 91%.

The overall average conversion value works out to be as high as 93%.

By-products obtained in the process consist of tetrahydrofuran (THF)-about 6% on a molar base with respect to the BDO produced.

Selectivity of the reaction is approx. 99% with respect to the overall amount of BDO and THF produced.

The high molar ratio between hydrogen and carbon monoxide favours the occurrence of methanol synthesis with stepwise conversion values higher than 90%.

The effluent from the reactor (Line 9) cools down in exchanger 10, letting heat to the recycle hydrogen rich stream, and in exchanger 11. Eventually it feeds (Line 20) separator 12 where the condensed organic phase separates from the hydrogen rich gaseous phase.

The gaseous phase coming out of separator 12 (Line 13) is compressed by compressor 14 to be recycled into the reaction system.

A small fraction of the recycle gas is purged (Line 15) to minimise the accumulation of inert materials.

The compressed gas (Line 16) and the feed hydrogen and carbon monoxide (Line 17), partly (Line 7) blend with the effluents from the first stage of reaction 6, and partly (Line 18) pre-heat in exchanger 10 and in terminal heater 19, to subsequently feed (Line 4) vapouriser 3.

The liquid phase coming out of separator 12 feeds (Line 21) product fractionation unit 22, where THF (Line 23), MOH (Line 24), water and light organic by-

products (Line 25), an unconverted GBL rich organic fraction (Line 2) bound to be recycled for hydrogenation, heavy organic by-products (Line 26) and BDO (Line 27) separate.

The innovative aspect of the process object of the present invention is better emphasised by a comparison of its performances of which above with those obtained carrying out the hydrogenation with the same shot and operating conditions, nevertheless without streaming any carbon monoxide gas.

It was found that without carbon monoxide, hence without any MOH synthesis, keeping the same high selectivity values, the overall conversion of GBL to DMS decreases from the 93% mark, obtained when feeding carbon monoxide, to approx. 84 %.

The lower conversion rates entice higher investment and production costs, both in the hydrogenation section, and in the subsequent distillation sections where the unconverted fractions bound to be recycled for hydrogenation are separated.

CLAIMS

1. A process for the production of 1,4-butanediol by vapour phase selective hydrogenation of gamma-butyrolactone, maleic or succinic anhydride methyl esters or mixtures of gamma-butyrolactone with the esters thereof, characterised by the fact that synthesis methanol is coproduced by feeding hydrogen gas enriched with carbon monoxide to the reaction.

2. A process according to claim 1, characterised in that the molar ratio between carbon monoxide and shot ester ranges between 0.1 and 1.0

3. A process according to claims 1 and 2, characterised in that the hydrogen to shot ester molar ratio ranges between 200 and 800.

4. A process according to claims 1,2 and 3, characterised in that its operating pressure ranges between 75 and 100 bars, and its operating temperature ranges between 170° and 230°C.


5. A process according to claims 1,2,3 and 4, characterised in that the hydrogenation catalyst is of the copper-zinc oxide or stabilised cuprous chromite type, with surface area never any smaller than 40 m²g⁻¹.

6. A process according to claim 5, characterised in that the vapour phase mixture containing shot hydrogen and ester contacts the catalyst

with a liquid hourly space velocity ranging between 0.1 and 1.0 hr⁻¹.

1/1

Fig. 1



INTERNATIONAL SEARCH REPORT

National Application No

PCT/EP 99/02297

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C07C29/136 C07C31/20

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 584 419 A (SHARIF MOHAMMAD ET AL) 22 April 1986 (1986-04-22) cited in the application column 4, line 42 - line 44; claim 1; example 1; table IV	1-6
Y	EP 0 722 923 A (STANDARD OIL CO OHIO) 24 July 1996 (1996-07-24) page 3, line 19 - line 21; claims 1-3	1-6

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

11 August 1999

Date of mailing of the international search report

18/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Arias-Sanz, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/02297

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4584419	A	22-04-1986	CA 1246616 A	13-12-1988
			EP 0143634 A	05-06-1985
			JP 61022035 A	30-01-1986
<hr/>				
EP 0722923	A	24-07-1996	US 5473086 A	05-12-1995
			AT 178878 T	15-04-1999
			CN 1129206 A	21-08-1996
			DE 69509060 D	20-05-1999
			DE 69509060 T	05-08-1999
			ES 2130538 T	01-07-1999
			JP 8193040 A	30-07-1996
<hr/>				